

**COMP 410  
Summer 2024**

**Final Practice Exam**

The final exam is cumulative, so all handouts, labs, practice exams, and prior exams are relevant. You may bring three 8.5 x 11 inch sheets of paper into the exam, and have handwritten notes on both sides of both sheets. This practice exam only covers material since exam 2, so it focuses on performing logic programming in Python.

1.) Consider the following Prolog procedure:

```
isName(alice).  
isName(bob).  
isName(janet).  
isName(bill).
```

Write an equivalent generator function in Python, named `isName`. Each name should be represented as a string. As a hint, `isName` should not take any parameters.

2.) Consider the following Prolog procedure:

```
naturalNumber(0).  
naturalNumber(N) :-  
    naturalNumber(NMinusOne),  
    N is NMinusOne + 1.
```

Write an equivalent generator function in Python, named `naturalNumber`. As a hint, `naturalNumber` should not take any parameters.

3.) Consider the following Prolog procedure:

```
selectElement([Head|_], Head).
selectElement(_|Tail, Element) :-
    selectElement(Tail, Element).
```

Write an equivalent generator function in Python, named `selectElement`. You can assume you have the following definitions available for representing lists:

```
class Nil:
    def __init__(self):
        pass

class Cons:
    def __init__(self, head, tail):
        self.head = head
        self.tail = tail
```

Example usage of `selectElement` is below:

```
for n in selectElement(Cons(1, Cons(2, Cons(3, Nil())))):
    print(n)
```

```
# Output:
# 1
# 2
# 3
```

4.) Consider the following Prolog procedure, which nondeterministically selects different values contained in a binary tree:

```
% tree ::= internal | node(tree, INT, tree)
treeElement(node(_, Value, _), Value).
treeElement(node(Left, _, _), Value) :-
    treeElement(Left, Value).
treeElement(node(_, _, Right), Value) :-
    treeElement(Right, Value).
```

The tree is represented in Python using the following two classes:

```
class Internal:
    def __init__(self):
        pass

class Node:
    def __init__(self, left, value, right):
        self.left = left
        self.value = value
        self.right = right
```

Write an equivalent generator function implementing `treeElement` in Python below.